

Model No.: YRB-6CT

Overview

YRB – Yixing Riser Box is able to hold up to 12 subscribers. It is used as a termination point for the drop cable to connect with patch cable in FTTH indoor application. It integrates fiber splicing, termination, storage and cable connection in one solid protection box.



SPECIFICATIONS

Item	Parameters
Scope of application	3.0x2.0mm drop cable or indoor cable
Fiber cladding diameter	125um(G652&G657)
Fiber diameter	250um&900um
Fiber type	SM&MM
Tensile strength	> 50 N
Operating temperature	-40 ~ +85 C
Connecting Adapter	SC & LC
Insertion loss	<0.2dB
Return loss	>50dB(UPC),>60dB(APC)

Features

- Dust-proof design with IP-45 Protection level.
- Integrated with splice cassette and cable management rods.
- Manage fibers in a reasonable fiber radius condition.
- Easy to maintain and extend the capacity.
- Suitable for the fusion splice or mechanical splice.
- Embedded type surface, easy for installation and removal.
- 12 ports cable entrance for patch cable.

Configuration

Material	PC+ABS
Size	A*B*C(mm) 150*104*30
Max Capacity	SC - 8 Ports / LC - 16 Ports
Mounting Way	Wall Mounting
Weight	0.2kg
Color	Green