


## FO passive components

### Optowire SC/APC-LC/APC Patch cord 2.0mm G657A2 LSZH simplex

- G.657.A2 Bend Insensitive Fiber & 10mm Min. Bend Radius
- Precision Zirconia Ferrule Connectors Ensure Low Loss
- LSZH Environmentally Friendly Jacket
- Optical Testing Ensures Network Performance
- Length – Customized



## TECHNICAL SHEET

<b>Connector A</b>	<b>SC/APC</b>	<b>Connector B</b>	<b>LC/APC</b>
<b>Fiber Mode</b>	<b>OS2 9/125<math>\mu</math>m</b>	<b>Fiber Count</b>	<b>Simplex</b>
<b>Fiber Grade</b>	<b>G.657.A2</b>	<b>Minimum Bend Radius</b>	<b>10mm</b>
<b>Polish Type</b>	<b>APC</b>	<b>Return Loss</b>	<b><math>\geq</math>60dB</b>
<b>Cable Jacket</b>	<b>LSZH</b>	<b>Cable Diameter</b>	<b>2.0 mm</b>
<b>Wavelength</b>	<b>1310/1550nm</b>	<b>Attenuation at 1310nm</b>	<b>0.36 dB/km</b>
<b>Insertion Loss</b>	<b><math>\leq</math>0.3 dB</b>	<b>Attenuation at 1550nm</b>	<b>0.22 dB/km</b>
<b>Operating Temperature</b>	<b>-20~70°C</b>	<b>Storage Temperature</b>	<b>-40~80°C</b>